

## H.264+ Ai Cameras (smart detection by human movements)

Picture			
Model	CAM6042FIR-AEF	CAM6042FIR-APC	CAM6023FIR-APC
2-Way Audio	Yes	Yes	Yes
Lens	4.2X, 2.8-12mm	4.2X, 2.8~12mm	4.2X, 2.8~12mm
Day/Night	IR-40M	IR-40M	IR-40M
Max Resolution	1920x1080@30FPS(2M)	1920x1080@30FPS(2M)	1920x1080@30FPS(2M)
I / O	Yes	Yes	Yes
IP66 / IK10	IP66/IP68	IP66/IP68	IP66/IP68/IK10

## H.264+ Special Cameras

Picture						
Model	CAM6039FIRS-POE (Anti-Corrosion)	CAM6059FIRS-POE (Anti-Corrosion)	CAM6053FIRS-POE (Anti-Corrosion)	CAM6049FICRS (Explosion)	CAM6048FICRS (Explosion)	CAM6058FICRS (Explosion)
2-Way Audio	Yes	Yes	Yes	Yes	Yes	Yes
Lens	4.2X, 2.8-12mm	10X, 5~50mm	4.2X, 2.8-12mm	4.2X, 2.8-12mm	10 x Optical Zoom	30 x Optical Zoom
Day/Night	IR-45M	IR-80M	IR-35M	Yes	Yes	Yes
Max Resolution	1920x1080@30FPS(2M)	1920x1080@30FPS(2M)	1920x1080@30FPS(2M)	1920x1080@30FPS(2M)	1920x1080@30FPS(2M)	1920x1080@30FPS(2M)
I / O	Yes	Yes	Yes	Yes	Yes	Yes
IP66 / IK10	IP68/ IP69	IP68/ IP69	IP68/ IP69/IK10	IP68, IP69, IK10	IP68, IP69, IK10	IP68, IP69, IK10

## 360 Panoramic Dome Cameras (software dewarp)

Picture	
Model	CAM6063UIRVS-POE
2-Way Audio	Yes
Lens	1.08mm
Day/Night	IR-20M
Max Resolution	3840x2160@30FPS (8M)
I / O	Yes
IP66 / IK10	IP68, IK10

## H.264+ Speed Domes

Picture		
Model	CAM6080QIR-POE-A	CAM6030FIR-POE-A
2-Way Audio	No	Yes
Lens	10x Optical Zoom	30x Optical Zoom
Day/Night	IR-70M	IR-150M
Max Resolution	2592x1944 @30FPS(5M)	1920x1080@30FPS (2M)
I / O	Yes	Yes
IP66 / IK10	IP66	IP66

## H.264+ 8MP Camera Series

Picture			
Model	CAM6883UIR-PoE	CAM6882UIR-PoE	CAM6063UIRVS-POE
2-Way Audio	Yes	Yes	Yes
Lens	2.8-13.5mm 4.8X	2.8-13.5mm 4.8X	1.08mm
Day/Night	IR-40M	IR-40M	IR-20M
Max Resolution	3840x2160@30FPS(8M)	3840x2160@30FPS(8M)	3840x2160@30FPS(8M)
I / O	Yes	Yes	Yes
IP66 / IK10	IP66/IP68/IK10	IP66/IP68	IP68, IK10



## H.264+ 5MP Camera Series

Picture				
Model	CAM6085QIR-POE	CAM6095QIR-AUTO	CAM6098QIR-AUTO	CAM6083QIR-POE
2-Way Audio	1-Way	Yes	Yes	Yes
Lens	3.6mm	4.2X, 2.8~12mm	10X, 5.1~51mm	2.8~12mm
Day/Night	IR-30M	IR-50M	IR-70M	IR-40M
Max Resolution	2592x1944 @30FPS(5M)	2592x1944 @30FPS(5M)	2592x1944 @30FPS(5M)	2592x1944 @30FPS(5M)
I / O	NA (Option)	Yes	Yes	Yes
IP66 / IK10	IP66	IP66/IP68	IP66/ IP68	IP66 / IP68/ IK10



## H.264+ 1080P Camera Series

Picture						
Model	CAM6023FIR-POE	CAM6024FIR-Auto	CAM6029FIR-POE	CAM6024FIRS-POE	CAM6042FIRS-AUTO	CAM6042FIRS-POE
2-Way Audio	Yes	Yes	1-Way	Yes	Yes	Yes
Lens	2.8~12mm	4.2X 2.8~12mm	3.6mm	2.8~12mm	4.2X, 2.8~12mm	2.8~12mm
Day/Night	IR-40M	IR-40M	IR-10M	IR-40M	IR-40M	IR-40M
Max Resolution	1920x1080@30FPS(2M)	1920x1080@30FPS(2M)	1920x1080@30FPS(2M)	1920x1080@30FPS(2M)	1920x1080@30FPS(2M)	1920x1080@30FPS(2M)
I / O	Yes	Yes	NA	Yes	Yes	Yes
IP66 / IK10	IP66 /IP68/ IK10	IP66 /IP68/ IK10	NA	N/A	IP66/ IP68	IP66/ IP68






## H.264 1080P Fixed-Lens Cameras

Picture		
Model	CAM6259FIR-PoE	CAM6229FIR-POE
2-Way Audio	NA	1-Way
Lens	3.6mm	3.6mm
Day/Night	IR-20M	IR-10M
Max Resolution	1920 x1080@30FPS	1920x1080@30FPS
I / O	NA	NA
IP66 / IK10	IP66	NA

## H.264+ Linux NVR

Picture		
Model	NVR6309L/ 6316L(P)	NVR6536L(LP)
Description	9/16CH P2P, POE (Optional)	36CH P2P, POE (Optional)
Storage	8 megapixel image quality Supports up to 16 cameras Support hard disk x 2 Fault detection warning	8 megapixel image quality Supports up to 49 IP cameras Support hard disk x 9 Fault detection warning Gigabits Ethernet Port X 2 Support 8 POE (optional)
Raid	NA	RAID-1,RAID-5 (optional)

Windows Server Type NVR Series (with external Video Management Software)

<b>Picture</b>					
<b>Model</b>	ALS-8N-H	ALS-16N-H	ALS-24N-H	NVR7000	NVR7000-RAID
<b>Description</b>	Up to 2M-100CH	Up to 2M-100CH	Up to 2M-100CH	Up to 2M-100CH	Up to 2M-100CH
<b>Storage</b>	Up to 8 megapixel image quality Hard-swap HDD Slot x 8 Gigabits Ethernet Port X 2 Built in redundant power 875W+ 875W	Up to 8 megapixel image quality HDD Slot x 8 Gigabits Ethernet Port X 2 Built in redundant power 875W+ 875W	Up to 8 megapixel image quality HDD Slot x 8 Gigabits Ethernet Port X 2 Built in redundant power 875W+ 875W	Up to 8 megapixel image quality HDD Slot x 8 (hard-swap HDD slot -optional) Gigabits Ethernet Port X 2	Up to 8 megapixel image quality HDD Slot x 8 (hard-swap HDD slot -optional) Gigabits Ethernet Port X 2
<b>Raid</b>	RAID-1,RAID-5 (Optional)	RAID-1,RAID-5 (Optional)	RAID-1,RAID-5 (Optional)	NA	RAID-1,RAID-5 (Optional)